iD Classics Click Ultimate 55

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	33 Heavy
Commercial warranty (in years)		10 years
Residential warranty (in years)		20 years
Technical Characteristics	**Norm**	**Tarkett Value**
Total thickness	EN ISO 24346	6,50 mm
Wear layer thickness	EN ISO 24340	0,55 mm
Total weight	EN ISO 23997	10700 g/m²
Binder content	EN ISO 10582	Type I
Surface treatment		TEKTANIUM ®
Embossing in Register		Yes
Bevelled edges		4 sides
Installation method		Click
Performance for CE Marking	**Norm**	**Tarkett Value**
Declaration of Performance #	EN 14041	0197-0057-DoP-2026-01
Technical Performance	**Norm**	**Tarkett Value**
Dimensional stability	EN ISO 23999	≤ 0,10 %
Curl resultant to heat	EN ISO 23999	≤ |1| mm
Reaction to fire	EN 13501-1	Bfl-s1
Residual indentation	EN ISO 24343-1	≤ 0,10 mm
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction - ΔLw	EN ISO 717-2	19 dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)
Thermal resistance	EN ISO 10456	0,07 m²•K/W
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Good resistance
Slip resistance	EN 16165 Annex B	R10
Slip resistance (EN 13893)	EN 13893	Class DS (μ ≥ 0,30)
Peeling Resistance	EN ISO 24345	≥ 50N/50mm
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	**Norm**	**Tarkett Value**
Recyclability through ReStart®		Offcuts / Post-use - Contact Tarkett for more information
Recycled content	ISO 14021	20 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		11,25 kg CO_2eq /m²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		6,08 kg CO_2eq /m²
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m³)
Dimensions and designs		
Plank	Plank 1200 x 200,5mm - 8 planks=1,92 m²/box - 40 boxes/pallet - 76,8 m²/pallet	
Tile	Tile 640 x 320mm - 9 tiles=1,84 m²/box - 40 boxes/pallet - 73,6 m²/pallet Tile 960 x 480mm - 4 tiles=1,84 m²/box - 42 boxes/pallet - 77,28 m²/pallet	
Number of designs available	30	

Embossing in Register available on only 6 CLASSICS designs.

The above information is subject to modification for the benefit of further improvement (25/08/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.