STYLE EMME XF² - 2,5mm

Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 24011	Plain and decorative linoleum
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	34 Very Heavy
Industrial classification	EN ISO 10874	43 Heavy
Technical Characteristics	**Norm**	**Tarkett Value**
Surface treatment		xf²™
Total thickness	ISO 24346	2,50 mm
Total weight	ISO 23997	2900 g/m²
Flexibility	ISO 24344 Method A	≤ 30 mm ⌀ Average measured value : 17,5 mm ⌀
Performance for CE Marking	**Norm**	**Tarkett Value**
CE Marking	EN 14041	EN 14041
Declaration of Performance #	EN 14041	0200-0001-DoP-2026-01
Reaction to fire - Glued on non-combustible substrate	EN 13501-1	Cfl-s1
Slip resistance	DIN 51130	R9
Slip resistance (EN 13893)	EN 13893	Class DS (μ ≥ 0,30)
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal conductivity (W/m K)	EN ISO 10456	0.17
Technical Performance	**Norm**	**Tarkett Value**
Residual indentation	EN ISO 24343-1	≤ 0,15 mm Average measured value: ca. 0,08 mm
Impact sound reduction - ΔLw	EN ISO 10140-3 / 717-2	6 dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)
Castor chair	EN ISO 4918	Suitable for office chairs with castors type W (Norm EN 12529)
Chemical resistance	ISO 26987	Resistant to dilute acids, oils, fats, current solvents and alkalis
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Light fastness	ISO 105-B02	≥ 6
Determination of antibacterial activity	ISO 22196	Naturally antibacterial (Bacteria mix - Ecoli and MRSA)
Sustainability performances	**Norm**	**Tarkett Value**
Recyclability through ReStart®		Offcuts / Post-use - Contact Tarkett for more information
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		-1,70 kg CO_2eq /m²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		-1,92 kg CO_2eq /m²
Recycled content		36 %
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m³)
Dimensions and designs		
Roll		Roll 2 x ≤30m Roll 2 x ≤32m
Number of designs available		48

Impact sound reduction with Elafono* - ΔLw (EN ISO 10140-3 / 717-2) : 14dB

*Elafono : 2,0mm traditional, 100% natural corkment underlay to be installed in combination with any compact Tarkett linoleum to get additional sound reduction (up to 15dB, depending on the product).

ENVIRONMENTAL MANAGEMENT SYSTEM ISO 14001 | ANTI-BRIBERY MANAGEMENT SYSTEM ISO 37001 | OCCUPATIONAL HEALTH AND SAFETY MANAGEMENT SYSTEMS ISO 45001 | ENERGY MANAGEMENT SYSTEM ISO 50001 | QUALITY SYSTEM ISO 9001 | SOCIAL ACCOUNTABILITY SA 8000

The above information is subject to modification for the benefit of further improvement (29/04/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.