# *Style Elle xf²- 2,5mm*

## Datasheet

| Classification | Norm | Tarkett Value |
|---|---|---|
| Product type | ISO 24011 | Plain and decorative linoleum |
| Domestic classification | EN ISO 10874 | 23 Heavy |
| Commercial classification | EN ISO 10874 | 34 Very Heavy |
| Industrial classification | EN ISO 10874 | 43 Heavy |
| **Technical Characteristics** | **Norm** | **Tarkett Value** |
| Surface treatment | | xf²™ |
| Total thickness | ISO 24346 | 2,50 mm |
| Total weight | ISO 23997 | 2900 g/m² |
| Flexibility | ISO 24344 Method A | ≤ 30 mm ⌀<br>Average measured value : 17,5 mm ⌀ |
| **Performance for CE Marking** | **Norm** | **Tarkett Value** |
| CE Marking | EN 14041 | EN 14041 |
| Declaration of Performance # | EN 14041 | 0200-0001-DoP-2026-01 |
| Reaction to fire - Glued on non-combustible substrate | EN 13501-1 | Cfl-s1 |
| Slip resistance | DIN 51130 | R9 |
| Slip resistance (EN 13893) | EN 13893 | Class DS (μ ≥ 0,30) |
| Static Electrical Propensity | EN 1815 | Antistatic (≤ 2 kV) |
| Thermal conductivity (W/m K) | EN ISO 10456 | 0.17 |
| **Technical Performance** | **Norm** | **Tarkett Value** |
| Residual indentation | EN ISO 24343-1 | ≤ 0,15 mm<br>Average measured value: ca. 0,08 mm |
| Impact sound reduction - ΔLw | EN ISO 10140-3 / 717-2 | 6 dB |
| Reduction of in-room impact noise | NF S31-074 | Class C (≤ 85 dB) |
| Castor chair | EN ISO 4918 | Suitable for office chairs with castors type W (Norm EN 12529) |
| Chemical resistance | ISO 26987 | Resistant to dilute acids, oils, fats, current solvents and alkalis |
| Underfloor heating | | Suitable (subfloor temperature maximum 27°C) |
| Light fastness | ISO 105-B02 | ≥ 6 |
| Determination of antibacterial activity | ISO 22196 | Naturally antibacterial (Bacteria mix - Ecoli and MRSA) |
| **Sustainability performances** | **Norm** | **Tarkett Value** |
| Recyclability through ReStart® | | Offcuts / Post-use - Contact Tarkett for more information |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3) | | -1,70 kg $CO_2$eq /m² |
| Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario) | | -1,92 kg $CO_2$eq /m² |
| Recycled content | | 36 % |
| Total VOC Emissions (after 28 days) | EN 16516 | Platinum (≤ 10 µg/m³) |
| **Dimensions and designs** | | |
| Roll | | Roll 2 x ≤30m |
| Number of designs available | | 9 |

Impact sound reduction with Elafono* - ΔLw (EN ISO 10140-3 / 717-2) : 14dB

*Elafono : 2,0mm traditional, 100% natural corkment underlay to be installed in combination with any compact Tarkett linoleum to get additional sound reduction (up to 15dB, depending on the product).

ENVIRONMENTAL MANAGEMENT SYSTEM ISO 14001 · ANTI-BRIBERY MANAGEMENT SYSTEM ISO 37001 · OCCUPATIONAL HEALTH AND SAFETY MANAGEMENT SYSTEMS ISO 45001 · ENERGY MANAGEMENT SYSTEM ISO 50001 · QUALITY SYSTEM ISO 9001 · SOCIAL ACCOUNTABILITY SA 8000 · xf² · 12 year GUARANTEE COMMERCIAL USE · RECYCLABLE OFFCUTS & POST-USE · PHTHALATE FREE · 36% RECYCLED CONTENT · 94% NATURAL INGREDIENTS · 76% RENEWABLE CONTENT · VOC ≤10µg/m³ OPTIMAL INDOOR AIR QUALITY · MADE IN ITALY · Potential contribution to GREEN BUILDING CERTIFICATIONS · CERTIFIED · Declare · cradle to cradle SILVER · BLUE ANGEL · floor score · A+ · M1 EMISSION CLASS FOR BUILDING MATERIALS

The above information is subject to modification for the benefit of further improvement (20/08/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

Tarkett