Technical Datasheet

Wet substrate underlayer
TarkoLay HO

UNDERLAYS

DESCRIPTION

Loose laid underlayer made of PVC coated glass fiber with studs to manage damp substrates

KEY FEATURES:

- Ready-to-use solution that can be installed on damp subfloor (up to 96% RH).
- Quicker and less expensive solution than waiting for lower RH in substrate.
- Easy to handle and install.
- Loose-lay solution easy to remove, with no damage to the substrate.



Subfloor type & applications:
- Residential and commercial applications.
- Wood, concrete subfloors.

Compatible flooring:
- Compact homogeneous vinyl in rolls.
- iQ Granit acoustic and iQ Natural acoustic.

MAIN SEGMENTS OF APPLICATION:

TECHNICAL INFORMATION

Product	
Size (m)	45 length x 2 width
Thickness (mm)	Total: 1.5 Studs: 0.3
Total weight (g/m2)	1700
Packaging	
Roll diameter (cm)	33
Roll weight (kg) with chuck	153
Min. order	1 roll

CLEANING & MAINTENANCE

No cleaning or maintenance required.

INSTALLATION

- The subfloor must be hard, clean, dry, free from cracks and contaminations and not exposed to moisture over 96% RH.
- Fully loose laid towards the substrate.
- Laying direction: install TarkoLay HO and HO in the same direction, the joints of the TarkoLay HO and of the HO must have an offset in relation to each other by about 20 cm.
- Use ventilated skirtings but never lock the flooring.
- All traffic must be restricted for 24 hours after installation.
- No heavy traffic or furniture placement for 72 hours after installation.

ARTICLE CODE

	SAP Code	EAN Code
Orange	313978001	4823078721013

Tarkett