Technical Datasheet

Acoustic comfort underlayer Elafono

UNDERLAY & OVERLAY SOLUTIONS

DESCRIPTION

Underlayer made of cork to enhance acoustic comfort choosing the natural route.

Key features:
- High-performance acoustic insulation reducing both impact sound reduction up to 15 dB, and in-room noise up to 65 dB, with any compact linoleum.
- 100% natural and sustainable backing layer.
- Highly flexible to ease installation.
- Superior performances in static indentation, thermal resistance and underfoot comfort.

Subfloor type & applications:
- Commercial applications.
- Concrete surfaces.

Compatible flooring:
- Compact linoleum in rolls.
- Heterogeneous and homogeneous vinyls in rolls.

Main segments of application:





INSTALLATION

- Unroll and acclimatize in the room for at least 24 hours (> 18°)
- Switch off 48 hours before installation the underfloor heating system, and remain it off at least 48 hours after.
- The subfloor must be flat, level, clean, without marks, sound, dry, solid, hard, smooth and not exposed to moisture.
- Install underlayer with the jute backing facing upwards and edge to edge
- Install Elafono and Linoleum flooring in the same direction. Use acrylic adhesive for linoleum flooring. Pay attention to the waiting time for such adhesive - read the installation instructions.
- The joints of the Elefano and of the linoleum must have a gap of at least 50cm.

TECHNICAL INFORMATION

Product

Size (m)	30 length x 2 width
Thickness (mm)	2.0
Total density (g/m^2)	1450

Packaging

Min. order	1 roll (also available as 608 x 608mm pre-cuts for access floor producers)

CLEANING & MAINTENANCE

No cleaning or maintenance required.

ARTICLE CODE

		SAP Code	EAN Code
	Brown	1861030	8022211100548

Tarkett

The above information is subject to modification for the benefit of further improvement. (11/20).