Technical Datasheet

Acoustic comfort underlayer Tarkomfort Premium - 2024

UNDERLAY & OVERLAY SOLUTIONS

DESCRIPTION

Extruded polystyrene foam underlay for enhanced acoustic performance with an “accordion” format. Specially designed to tackle noise for floating installation.

Key features:

- High-performance acoustic insulation: high-impact sound reduction (18 dB with iD Inspiration Click Solid 30 & 55) and in-room noise reduction (72 dB).
- High-performance solution with good static indentation resistance (0.07mm with iD Inspiration Click Solid 30 & 55) and high compressive strength >400kPa.
- Thermal resistance strandard respected: 0,03 m²/W
- Minimal thickness, ideally suited for renovation.
- Quick and easy to install: 1m roll to be handled and light weighted.
- Loose-lay for easy removal at end of life.
- Available in 12.5lm format

Subfloor type & applications:

- Residential and commercial applications.
- Screed, concrete surfaces, floorboards.
- Compatible with underfloor heating.

Compatible flooring:

- iD Inspiration Click Solid 30 & 55

Main segments of application:





INSTALLATION

- Unroll and acclimatize in the room for at least 48 hours (> 18°).
- The subfloor must be dry and clean.
- Fully loose-laid on the substrate.

TECHNICAL INFORMATION

Product	
Size (mm)	12,5 length x 1.2 width
Thickness (mm)	1.0
Total density (kg/m²)	130 (1.95kg/roll)

ARTICLE CODE

		SAP Code
	Blue 15 lm	24992900

CLEANING & MAINTENANCE

No cleaning or maintenance required.

Tarkett