ProtectWall CR (CLEAN ROOMS)

Datasheet

Classification	Norm	Tarkett Value
Product type	EN 259-1	Heavy Duty Wall Covering
Technical Characteristics	**Norm**	**Tarkett Value**
Total thickness	EN ISO 24346	1,50 mm
Total weight	EN ISO 23997	2400 g/m²
Wear layer thickness	EN ISO 24340	0,15 mm
Surface treatment		Top Clean XP
Installation method		Glue-Down
Performance for CE Marking	**Norm**	**Tarkett Value**
Declaration of Performance #	EN 15102	0132-0065-DoP-2022-10
Reaction to fire	EN 13501-1	B-s2,d0 glued on any non-metal A1 or A2-s1,d0 class substrate
Technical Performance	**Norm**	**Tarkett Value**
Light fastness	ISO 105-B02	≥ 6
Impact Resistance	EN 259-2	Resistant to impacts - No visible burst nor crack
Chemical resistance	ISO 26987	Not affected
Spongeability, washability, lyability, brushability	EN 12956	Super washable and brushable
Determination of Flexibility	ISO 24344 - EN 435	No damage, no crack
Bacteria Resistance	ISO 846 part A and C	Does not promote growth
Riboflavin Test	ISO 4628-1 - VDI 2083 P17	Class 0 : Excellent
Clean room	ISO 14644-1	Clean room suitable
Ease of Decontamination	ISO 8690	Good
Sustainability performances	**Norm**	**Tarkett Value**
Recyclability through ReStart®		Offcuts - Contact Tarkett for more information
Recycled content		20 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		4,44 kg CO_2eq /m²
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 µg/m³)
Formaldehyde emission		E1
Dimensions and designs		
Roll		Roll 2 x 20 m
Number of designs available		2

The above information is subject to modification for the benefit of further improvement (12/10/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.