ForGrid P

UNIAXIAL GEOGRIDS - COMMERCIAL PRODUCT RANGE

Commercial Product Range & Quick Reference - high-tenacity PET geogrids with polymeric coating

Product	Tult MD (kN/m)	Tult CD (kN/m)	Elongation MD / CD (%)	Mesh MD / CD (mm)	Roll size W × L (m)	Area / roll (m²)
ForGrid P 40/20	≥ 40	≥ 20	10 / 10	29 × 29	5.25 × 100	525
ForGrid P 60/20	≥ 60	≥ 20	10 / 10	29 × 29	5.25 × 100	525
ForGrid P 80/20	≥ 80	≥ 20	10 / 10	29 × 29	5.25 × 100	525
ForGrid P 100/20	≥ 100	≥ 20	10 / 10	29 × 29	5.25 × 100	525
ForGrid P 110/20	≥ 110	≥ 20	10 / 10	29 × 29	5.25 × 100	525
ForGrid P 120/20	≥ 120	≥ 20	10 / 10	29 × 29	5.25 × 100	525
ForGrid P 150/20	≥ 150	≥ 20	10 / 10	25 × 29	5.25 × 100	525
ForGrid P 160/20	≥ 160	≥ 20	10 / 10	29 × 29	5.25 × 100	525
ForGrid P 180/20	≥ 180	≥ 20	10 / 10	29 × 29	5.25 × 100	525
ForGrid P 200/20	≥ 200	≥ 20	10 / 10	29 × 29	5.25 × 100	525
ForGrid P 300/50	≥ 300	≥ 50	10 / 10	20 × 29	5.25 × 100	525
ForGrid P 600/50	≥ 600	≥ 50	10 / 10	15 × 27	5.25 × 50	262.5

COMMERCIAL NOTES

- Roll dimensions shown are nominal and availability shall be confirmed at quotation/order.
- Declared tolerances and complete technical characteristics are governed by the individual TDS / DoP.
- Product selection and suitability depend on the actual project conditions and design requirements.

Commercial product-range summary only. It does not replace the individual Technical Data Sheet or project-specific engineering design.